

ABSOLUTE V HT120

V-Bank Box Filter



ADVANTAGES

- High filter surface area offers low pressure drop for energy savings and longer life
- Large media area
- High airflow rates
- Withstand high temperature up to 120°C

Application	Industry and hospitals
Type	V-Bank Box Filter
Frame	Galvanised steel
Gasket	EPDM
Media	Glass fiber
Separator	Glassfiber
Sealant	Polyurethane
Temperature max	120°C
Installation Options	Mounting systems: FCBL-A housing
Comment	Gasket: Half-round neoprene 0 15 mm moulded in one piece, 99.95% MPPS (H13 according to EN 1822), 99.99 % 0.3µ Temperature: 120°C maximum continuous

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
Absolute V HT 120	H13	610x610x292	2500/250	24	19
Absolute V HT120	H13	289x595x292	1300/250	16	12
Absolute V HT120	H13	595x595x292	3200/250	38	22
Absolute V HT120	H13	305x610x292	1500/250	16	13
Absolute V HT 120	H13	610x610x292	3400/250	33	20
Absolute V HT120	H13	610x610x292	4000/250	40	23