


CAMGT 3V-600

Compact Pleated Filter



ADVANTAGES

- Lowest air resistance (dP) for optimal economy
- Solid HEPA frame eliminates air bypass
- Patented aerodynamic grid
- Meets the industry's most stringent requirements
- Largest media area for longest life or higher airflows application
- High filtration efficiency (up to H13)
- Patented vertical pleat

Application	All installations where safety and reliability is crucial. Low air resistance, long life and high dust concentrations
Type	Compact Pleated Filter
Frame	Plastic moulded
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Grille, Downstream	Support grid for filtermedia
Rec. final pressure drop	600 Pa
Max airflow	1,8 x nominal flow
Temperature max	70°C
RH. max	100%
Comment	Burst strength: > 6250 Pa continuous wet/soaked.

The CamGT 3V-600 is built on a solid 600 mm deep frame with extended media area. The unique design provides industry-leading pressure drop and dust holding capacity ensuring optimum performance, low average pressure drop and a long filter life. The filter is also available with CamBrane media in E12 efficiency.

Media	EN779	EN1822	ISO 16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)	ASHRAE 52.2-2017
Glass fiber	F8		ePM1 80%	592x592x600	4250/100	41	15	MERV 14
Glass fiber	F9		ePM1 85%	592x592x600	4250/115	38	15	MERV 15
Glass fiber		E10		592x592x600	4250/135	45	16	MERV 16
Glass fiber		E11		592x592x600	4250/140	48	16	
Glass fiber		E12		592x592x600	4250/190	50	17	
Membrane		E12		592x592x600	4250/190		19	
Glass fiber		H13		592x592x600	4250/240	50	17	