

# CAM-FLO GT HYBRID

Bag Filter



## ADVANTAGES

- Conical bag for improved airflow
- Maximum surface use for high dust holding capacity
- Incinerable bags
- Recommended choice for gas turbine pre-filtration
- Hybrid technology media
- Thick synthetic pre-filter layer for high mechanical strength and coalescing properties
- A fine fiber layer provides high efficiency with stable dP in high humidity

<b>Application</b>	Installations exposed to turbulence and harsh environments
<b>Type</b>	Bag Filter
<b>Frame</b>	Galvanised steel
<b>Media</b>	Hybrid Synthetic and Glass Technology
<b>Rec. final pressure drop</b>	450 Pa
<b>Temperature max</b>	70°C
<b>Comment</b>	Additional information: Available in half - and special size filters on request

The Cam-Flo Hybrid is a new generation of premium bag filters for gas turbines that utilize the breakthrough Hybrid media technology to combine glass fiber and synthetic fibers. The results is a smart solution for an extended filter life, a stable and predictable performance, and most of all, carefree operations. Self-supporting bags and a unique design make this filter an excellent pre-filter and coalescer choice for turbomachinery applications.

Model Name	EN779	ISO 16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Bags	Media area (m <sup>2</sup> )	Weight (kg)	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10	ASHRAE 52.2-2017
Cam-Flo GT Hybrid F7	F7	ePM1 60%	592x592x640	4250/90	10 (std)	7,5	2.45	60	60	71	71	90	MERV 13